


1551 S. Vineyard Avenue Ontario, CA 91761 (909) 923-1973


WIRING SCHEMATICS


BASIC AUTOMOTIVE CONVERSION WITH DUAL MOTOR

FOR SOFTWARE VERSIONS 5.00 AND HIGHER FOR CURTIS CONTROLLERS 1234/1236/1238

REVISION: A Date: 4/25/2013







REVISIONS NOTICE: This drawing is the property of Hi Performance Electric Vehicle Systems Inc., and/or its subsidiaries and affiliates (individually and collectively "HPEVS"), and contains highly proprietary, confidential, and trade secret DESCRIPTION APPROVED information of HPEVS. The recipient of this drawing agrees (a) to use the information contained herein for the INITIAL RELEASE 3/11/2013 purpose for which it was furnished by HPEVS (b) to return this drawing upon HPEVS request. This notice shall appear on any complete or partial reproduction of this drawing. VEHICLE +12V Vehicle + 12V CHASSIS CAN HIGH GROUND CAN LOW **CANOP ISOLATOR MODULE** CONTROLLER CAN HIGH **VEHICLE ISOLATED** CAN LOW CAN NETWORK +12V Controller** ** DO NOT CONNECT THE +12V FROM CONTROLLER TO CAN ISOLATOR CAD TYPE CAD LOC. CAD FILE DRW SIZE A VISIO DRAWING OPER. NO. UNIT 1010-CAN-OP-ISOLATOR DESIGN DETAIL TITTLE **CAN ISOLATOR** CHECKED SAFETY SCALE DATE 4/17/13 REVISION A **HPEVS** NONE OF 1 SHEET 1

THROTTLE CONFIGURATION

Depending of the type of throttle used for the application, see below table to determine the appropriate connection. Electrical schematics are also included in page 7 through 9.

THROTTLE CONFIGURATION	TYPE	ELECTRICAL CONNECTIONS
2 WIRE with SWITCH 0-5k Ω	TYPE 2	Connect PURPLE / WHITE wire labeled #18 with PURPLE / WHITE wire. Ending connection at throttle pot low. YELLOW / WHITE wire connected to throttle wiper
		Connect BLACK / WHITE wire labeled #15 with BLACK/ WHITE wire. Ending connection at throttle pot high. Connect PURPLE / WHITE wire labeled #18 WITH PURPLE / WHITE wire. Ending connection at throttle pot low.
3 WIRE with SWITCH 0-5k Ω	TYPE 3	Connect YELLOW / WHITE wire connected to throttle wiper.
		Disconnect any wire connected to BLACK/WHITE wire labeled #15. Disconnect any wire from PURPLE/ WHITE wire labeled #18.
		Connect BLACK /BLUE WIRE LABELED #7 with BLACK/ BLUE wire. Ending connection at electronic throttle ground.
FLECTRONIC		Connect RED/ WHITE wire labeled #26 with PURPLE / WHITE wire. Ending connection at throttle +5V input.
ELECTRONIC without SWITCH	TYPE 1	Connect YELLOW / WHITE wire to electronic throttle signal.

NOTICE: This drawing is the property of Hi Performance Electric Vehicle Systems Inc., and/or its subsidiaries and REVISIONS affiliates (individually and collectively "HPEVS"), and contains highly proprietary, confidential, and trade secret DESCRIPTION APPROVED information of HPEVS. The recipient of this drawing agrees (a) to use the information contained herein for the INITIAL RELEASE 1/22/2013 purpose for which it was furnished by HPEVS (b) to return this drawing upon HPEVS request. This notice shall appear on any complete or partial reproduction of this drawing. 2 WIRE TYPE 2 **THROTTLE** YELLOW / WHITE **POT LOW** PURPLE / WHITE NC RED/ BLUE COM NORMALLY CLOSED INTERLOCK SWITCH** **GREEN** ** When accelerator pedal IS PRESSED the interlock switch is released to its **NORMAL** position (switch not activated) thus completing the circuit since its green wire is connected to the normally closed (NC) connection. CAD TYPE CAD FILE CAD LOC. DRW SIZE A VISIO OPER. NO. UNIT DRAWING 1010-THROTTLE-001 DETAIL DESIGN TITTLE 2 WIRE TYPE 2 CHECKED SAFETY THROTTLE SCALE DATE 1/22/13 REVISION A **HPEVS** NONE SHEET 1 OF 3

NOTICE: This drawing is the property of Hi Performance Electric Vehicle Systems Inc., and/or its subsidiaries and REVISIONS affiliates (individually and collectively "HPEVS"), and contains highly proprietary, confidential, and trade secret DESCRIPTION APPROVED information of HPEVS. The recipient of this drawing agrees (a) to use the information contained herein for the INITIAL RELEASE 1/22/2013 purpose for which it was furnished by HPEVS (b) to return this drawing upon HPEVS request. This notice shall appear on any complete or partial reproduction of this drawing. BLACK / WHITE **POT HIGH** 3 WIRE TYPE 3 **WIPER THROTTLE** YELLOW / WHITE PURPLE / WHITE **POT LOW** NC RED/ BLUE COM NORMALLY CLOSED INTERLOCK SWITCH** **GREEN** ** When accelerator pedal IS PRESSED the interlock switch is released to its **NORMAL** position (switch not activated) thus completing the circuit since its green wire is connected to the normally closed (NC) connection. CAD TYPE CAD FILE CAD LOC. DRW SIZE A VISIO OPER. NO. UNIT DRAWING 1010-THROTTLE-001 DETAIL DESIGN TITTLE 3 WIRE TYPE 3 CHECKED SAFETY THROTTLE SCALE DATE 1/22/13 REVISION A **HPEVS** NONE SHEET 2 OF 3


NOTICE: This drawing is the property of Hi Performance Electric Vehicle Systems Inc., and/or its subsidiaries and REVISIONS affiliates (individually and collectively "HPEVS"), and contains highly proprietary, confidential, and trade secret DESCRIPTION APPROVED information of HPEVS. The recipient of this drawing agrees (a) to use the information contained herein for the purpose for which it was furnished by HPEVS (b) to return this drawing upon HPEVS request. This notice shall appear INITIAL RELEASE 1/22/2013 on any complete or partial reproduction of this drawing. **ELECTRONIC** BLACK / BLUE (BLACK IN 1239 CTRL) THROTTLE** GROUND YELLOW / WHITE SIGNAL **ELECTRONIC** THROTTLE PURPLE / WHITE +5V ** When Electronic pedal is used, the GREEN wire from pedal interlock does not need to be connected CAD TYPE CAD FILE CAD LOC. DRW SIZE A VISIO OPER. NO. UNIT DRAWING 1010-THROTTLE-001 DESIGN DETAIL TITTLE **ELECTRONIC THROTTLE** CHECKED SAFETY SCALE NONE DATE 1/22/13 REVISION A **HPEVS** SHEET 3 OF 3

PEDAL INTERLOCK CONNECTION

The pedal interlock connection is required for both 2 and 3 wire throttle pot assemblies. The Green wire is connected at Normally Closed tab. Red wire is connected at common tab. See below picture.

NOTE, when accelerator pedal <u>IS PRESSED</u> the interlock switch is released to its <u>NORMAL</u> position (switch not activated) thus completing the circuit since its green wire is connected to the normally closed (NC) connection.

Electronic throttles usually do not have an interlock switches. In this application, the Green and Red wires are connected together.



BRAKE POT CONFIGURATION

Depending of the type of brake pot used for the application, see below table to determine the appropriate connection. Electrical schematics are also included in page 12 & 13.

BRAKE POT CONFIGURATION	TYPE	ELECTRICAL CONNECTIONS
		Connect PURPLE / WHITE wire labeled #18 with PURPLE / WHITE wire. Ending connection at brake pot low.
2 WIRE 0-5k Ω	TYPE 2	Connect YELLOW / RED wire labeled #17 with wire YELLOW/ RED wire. Ending connection at brake wiper.
		Connect RED/ BLUE wire to brake transducer +12V input.
		Connect BLACK/ BLUE wire labeled #7 with Black/BLUE wire. Ending connection at brake transducer ground.
BRAKE TRANSDUCER	TYPE 1	Connect YELLOW / RED wire labeled #17 with wire YELLOW/ RED wire. Ending connection at brake transducer output signal.

REVISIONS NOTICE: This drawing is the property of Hi Performance Electric Vehicle Systems Inc., and/or its subsidiaries and affiliates (individually and collectively "HPEVS"), and contains highly proprietary, confidential, and trade secret APPROVED DESCRIPTION information of HPEVS. The recipient of this drawing agrees (a) to use the information contained herein for the purpose for which it was furnished by HPEVS (b) to return this drawing upon HPEVS request. This notice shall appear on any complete or partial reproduction of this drawing. INITIAL RELEASE 2/19/2013 2 WIRE BRAKE POT YELLOW / RED POT LOW PURPLE / WHITE CAD TYPE CAD LOC. CAD FILE DRW SIZE A VISIO OPER. NO. UNIT DRAWING 1010-BRAKE-001 DETAIL DESIGN TITTLE 2 WIRE CHECKED SAFETY **BRAKE** SCALE NONE DATE 2/19/13 REVISION A **HPEVS** SHEET 1 OF 2

